

HT1 Series

High Bay LED luminaires in a stylish troffer design for high ceiling applications that require superior lumen output, ultra-long life and high quality of light

Applications

- Automotive Showrooms
- Big Box Retailers
- Convention Centers
- Schools / Universities
- Warehouses



Lumen Range
12,000 to 24,000 lm



High Efficacy
up to 151LPW



Ultra-Long Life
L70 at 278,000 hours

Stylish Troffer Design

Clean and Harmonious Design

Mounting Options

Suspended / Recessed

Long Life

Up to L85 after 10 years (24/7)

Dimming & Sensors

0-10V / IoT ready / Optional sensors

Emergency Battery Backup

Optionally installed with 90 min. duration

5-year Warranty

10-year optional

Product Offering



Nominal Lumens	Size	Lumen Output ¹	Efficacy	Watts	Max. Ambient Temp.	Part Number
12000	2x2	12207	133	92	45°C	HT10S-A1-12K-22-50-80-FR-LV-GRID-10V
12000	2x4	12207	133	92	45°C	HT10S-A1-12K-24-50-80-FR-LV-GRID-10V
18000	2x2	18133	138	131	45°C	HT10S-A1-18K-22-50-80-FR-LV-GRID-10V
18000	2x4	18538	151	123	45°C	HT10S-A1-18K-24-50-80-FR-LV-GRID-10V
24000	2x4	24112	129	187	45°C	HT10S-A1-24K-24-50-80-FR-LV-GRID-10V

¹Typical at 277V (LV) and (25°C), 4000K/5000K, typical CRI 80+. 3500K multiplier is 0.93. Frosted Lens, +/-10%. No lens Lens multiplier is 1.08.

Flex Lighting Solutions

North America
 7320 W 162nd St.
 Overland Park
 KS 66085, USA

EMEA
 ul. Malinowska 28
 83-100 Tczew
 Poland

Australia
 359-361 City Rd
 Southbank, VIC 3006
 Australia

www.flexlightingsolutions.com · lighting.tech@flex.com · Phone: +1 (913) 851-3000